

General Relay

Main technical parameter



JJDZ3-33








MY2






MY3

Model		JJDZ3-33	MY2	MY3
Specifications				
Terminal layout		3Z	2Z	3Z
Contact capacity	AC	3A /28VDC 3A/220VAC	5A 250V	5A 250V
	DC		5A 30V	5A 30V
Contact resistance(mΩ)		≤50mΩ	≤50mΩ	≤50mΩ
Insulation resistance(MΩ)		≥500MΩ	≥100MΩ	≥100MΩ
Dielectric strength	BOC	1000VAC	1000VAC	1000VAC
	BCC	5000VAC	1500VAC	1500VAC
Coil nominal voltage	AC	6 to 220V	6 to 240V	6 to 240V
	DC		6 to 220V	6 to 220V
Coil nominal power	AC	≤3W	0.9VA to 1.2VA	0.9VA to 1.2VA
	DC		≤0.9W	≤0.9W
Electrical life(OPS)		10 ⁵	10 ⁵	10 ⁵
Mechanical life(OPS)		10 ⁷	10 ⁷	10 ⁷
Operating temperature(°C)		-30~+40	-40~+60	-40~+60
Weight(g)		85	≤35	≤35
Mounting methods		Outlet	Printed-circuit board, Outlet	Printed-circuit board, Outlet

Dimension



MY2



MY3