

Multi Range Timer

Main technical parameter



ST2P



ST3PA



H3BA-8/H3BA-11

Classification		Timer	Multi Range Timer		Multi Range Timer		
Model		ST2P	ST3PA		H3BA-8/H3BA-11		
Specification							
Dimension		50H×40W×57.5D	50H×40.5W×57.5D		48H×48W×93.5D		
Mounting & Socket	Surface(-N)	PF083A(E)	PF083A(E)		PF113A(E)	PF083A PS-08	
	Flush(-Y)	US-08 P3G-08	US-08 P3G-08		US-11	US-08 P3G-08	
Full Timing Range		SEC: 1,3,6,10,12,30,60 MIN: 3,6,10,12,30,60 HR: 3,6,10,12,30	A:0.05-0.5s/5s/30s/3min B:0.1-10s/60s/6min C:0.5-5s/50s/5min/30min D:1-10s/100s/100min/60min E:5-60s/10s/60min/6h F:0.25-2min/20min/2h/12h G:0.5-4min/40min/4h/24h		0.1SEC~100HRS		
Rated Voltage(V)		AC:12,24,110,220(50/60Hz) DC:12~24	AC: 24,48,110,220 (50/60Hz) DC: 24,48		24 to 240 DC/AC AC:24,48,110,220 DC:12,24,48		
Indicator Operating		ON-UP Operating	ON-UP Operating		Time Operating Flicker		
O/P Contact	Model	ST2P-E	ST3PA	ST3PC	H3BA	H3BA-8	H3BA-8H
	Time Limit 1C	5A		5A			5A
	Time Limit 2C	5A	5A		5A	5A	
	Instantaneous 1C	5A		5A			5A
Life	Mechanical	5×10 ⁷ Times	5×10 ⁷ Times		10 ⁷ Times		
	Electrical	10 ⁵ Times	10 ⁵ Times		10 ⁵ Times		
Accuracy	Repeat Error	±2% max	±2% max		±2% max		
	Setting Error	±5% max	±5% max		±5% max		
	Voltage Error	±5% max	±5% max		±5% max		
	Temp Error	±2% max	±2% max		±2% max		
Reset Time		0.5 sec max	0.5 sec max		0.5 sec max		
Consumed Power		3VA	3VA		100~240VAC:10VA 12VDC,24~240VDC:1.5W		
Ambient temperature		-10℃~+55℃	-10℃~+55℃		-10℃~+55℃		
Ambient Humidity		35~85% RH	35~85% RH		35~85% RH		
Weight		100g	100g		100g		