

Digital Timer

Main technical parameter



ASY-2D



ASY-3D



H3Y-□(ST6P)

Classification		Digital Timer	Digital Timer	Timer
Model		ASY-2D	ASY-3D	H3Y-□(ST6P)
Specification				
Dimension		88H×58W×68D	88H×58W×68D	28H×21W×52.6D
Mounting & Socket	Surface(-N)	PF083A	PF083A	PYF08A(E) PYF14A(E)
	Flush(-Y)	US-08 P3G-08	US-08 P3G-08	With Y-20 adapter
Full Timing Range		SEC: 9.9,99 MIN: 9.9,99 HR: 9.9,99	SEC: 9.99,99.9,999 MIN: 99.9,999 HR: 99.9,999	SEC: 1,3,5,10,30,60,120 MIN: 3,5,10,30,60 HR: 3
Rated Voltage(V)		AC:12,24,110,220,240 50/60Hz DC:12,24	AC:12,24,110,220,240 50/60Hz DC:12,24	AC:12,24,110,220,240 50/60Hz DC:12,24
Indicator Operating		After contact transfer	After contact transfer	Power,up Operating
O/P Contact	Model	ASY-2D	ASY-3D	
	Time Limit 1C			
	Time Limit 2C	5A	5A	
	Instantaneous 1C			
Life	Mechanical	5×10 ⁶ Times	5×10 ⁶ Times	5×10 ⁶ Times
	Electrical	10 ⁵ Times	10 ⁵ Times	10 ⁵ Times
Accuracy	Repeat Error	±0.05% max	±0.05% max	±3% max
	Setting Error	0	0	—
	Voltage Error	±0.05 Sec	±0.05 Sec	±2% max
	Temp Error	±0.05 Sec	±0.05 Sec	±5% max
Reset Time		0.3 sec max	0.3 sec max	0.2 sec max
Consumed Power		5VA	5VA	3VA
Ambient temperature		-10℃~+55℃	-10℃~+55℃	-10℃~+55℃
Ambient Humidity		48~85% RH	48~85% RH	48~85% RH
Weight		230g	230g	45g