

## DIN-RAIL KWH Meter

### Applications

ADM is a kind of electronic Din rail watt-hour meter. It completely accords with relevant technical requirements of class 1 and class 2. It can accurately and directly measure active energy consumption. It also can display total energy consumption by step type impulse register or LCD display. This watt-hour meter is according to EN62053-21.



ADM25SC



ADM65S



ADM100S



ADM100SC



ADM100TE

Conform to EN62053-21 Accuracy	class 1,2
Frequency	50/60Hz
Single phase	220-240V
Rated impulse voltage	Uimp 6KV-1.2/50S
Power consumption	≤1.5w/6VA per phase
Temperature range	-10°C-+50°C

Conform to EN62053-21 Accuracy	class 1,2
Frequency	50/60Hz
Three phase	3X380V,3X
Rated impulse voltage	Uimp10KV-1.2/50S
Power consumption	≤2w/10VA per phase
Temperature range	-10°C-+50°C

### Specification

Mounting: DIN rail EN 50022

TYPE	Rating	Voltage	Class	Designation
ADM25S	2.5(10)A	AC120V/230V	1.0/2.0	Single Phase 1 module
	3(15)A			
	5(25)A			
ADM65S	5(30)A	AC120V/230V	1.0/2.0	Single Phase 2 module
	2.5(10)A			
	3(15)A	AC230V		
	10(40)A			
ADM100S	15(60)A	AC120V/230V	1.0/2.0	Single Phase 4 module
	2.5(10)A			
	5(30)A	230V		
	10(50)A			
ADM100SC (LCD)	15(60)A	230V	1.0	Single Phase 4 module Multifunctional Meter(LCD Display)
	20(100)A			
	5(30)A			
	10(60)A			
ADM100SE (LED)	15(90)A	230V	1.0	Single Phase 4 module(LED Display)
	20(80)A			
	5(30)A			
	10(40)A			
ADM100T	20(100)A	230/400V	1.0	Three Phaes 7 module
	1.5(6)A CT			
	3(6)A CT	230/400V		
	5(30)A			
	10(60)A			
ADM100TC (LCD)	15(90)A	230/400V	1.0	Three Phaes 7 module Multifunctional Meter(LCD Display)
	20(100)A			
	1.5(6)A CT			
	3(6)A CT			
	5(30)A			